

Product Name: **Flash Point Reference Material  
– FPRM11**

Revision Date: *April 13, 2010*



Page 1 of 9

MSDS ref CII10-019

# MATERIAL SAFETY DATA SHEET

## SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT

**Product name:** **Flash Point Reference Material – FPRM11**

**Alternate description/ brand:** FPRM11

**Product description:** Undecane; hydrocarbon liquid

**Product code:** 9727-A15

**Intended use:** Flash Point Reference standard

### COMPANY IDENTIFICATION

**Supplier:** Cannon Instrument Company

2139 High Tech Road

State College, Pennsylvania 16803

Product Technical Information: (814) 353-8000

Product MSDS Information: (814) 353-8000

### EMERGENCY TELEPHONE NUMBER:

24-Hour Transportation Emergency: (800) 255-3924 Domestic CHEM-TEL Inc.

24-Hour Health Emergency: +1 (813) 248-0585 Overseas CHEM-TEL Inc. (please call collect)

## SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

### OSHA Hazardous Substance(s) or Complex Substance(s)

This product is hazardous as defined in 29 CFR1910.1200, based on the following:

<u>INGREDIENTS</u>	<u>CAS Number</u>	<u>Wt %</u>	<u>EINECS</u>	<u>SYM</u>	<u>R-Phrases</u>
Undecane	1120-21-4	100%	214-300-6	Xn	R65, R36/38

<u>OSHA HAZARD</u>	<u>COMPONENT</u>
Flammable	Undecane
Irritant	Undecane
Ingestion (aspiration hazard)	Undecane

## SECTION 3 HAZARD IDENTIFICATION

### EFFECTS OF OVEREXPOSURE:

#### Acute effects

**Eye:** Irritant

**Skin:** Irritant

**Inhalation:** High vapor/aerosol concentrations (attainable at elevated temperatures) are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness,

Product Name: **Flash Point Reference Material  
– FPRM11**

Revision Date: *April 13, 2010*



Page 2 of 9

MSDS ref CII10-019

anaesthesia, drowsiness, unconsciousness, and other central nervous system effects. This substance is unlikely to present a significant inhalation hazard if used for the recommended purpose.

**Oral:** Low toxicity. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause severe pulmonary injury, possibly progressing to death.

#### **Prolonged/ repeated exposure effects**

##### **Chronic effects**

None identified

#### **Signs and symptoms of overexposure:**

Irritation and/ or redness of eyes and skin

#### **Medical conditions aggravated by exposure**

None identified

**NFPA HAZARD ID:** Health: 0 Flammability: 2 Reactivity: 0  
(National Fire Protection Association)

NOTE: This material should not be used for any other purpose than the intended use in Section 1

### **SECTION 4 FIRST AID MEASURES**

**INHALATION** Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

**SKIN CONTACT** Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse.

**EYE CONTACT** Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

**INGESTION** If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

**NOTE TO PHYSICIAN:** Ingested material, if aspirated into the lungs, may cause chemical pneumonitis.

### **SECTION 5 FIRE-FIGHTING MEASURES**

#### **EXTINGUISHING MEDIA**

**Appropriate extinguishing media:** Carbon dioxide, foam, dry chemical and water fog. Water can be used to cool fire exposed containers

#### **FIRE FIGHTING**

**Fire fighting instructions:** Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid

spraying water directly into storage containers due to danger of boilover. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

**Unusual fire hazards:** None identified

**Hazardous combustion products:** Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products

#### GENERAL HAZARD

Combustible Liquid can form combustible mixtures at temperatures at or above the flashpoint. Static Discharge: Material can accumulate static charges which can cause an incendiary electrical discharge. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

#### FLAMMABILITY PROPERTIES

**Flash point °C (°F) [method]:** 65°C (149°F) [ASTM D56]

**Flammable limits (approx. Volume % in air) – not available**

**Autoignition temperature °C (°F):** 205 °C (400 °F)

### SECTION 6 ACCIDENTAL RELEASE MEASURES

**NOTIFICATION PROCEDURES :** Report spills/releases to appropriate authorities as required.

#### CONTAINMENT/ CLEANUP

**PROCEDURES IF MATERIAL IS RELEASED OR SPILLED:**

**LAND SPILL:** Shut off source taking normal safety precautions. Take measures to minimize the effects on ground water. Recover by pumping (use an explosion proof or hand pump) or contain spilled material with sand or other suitable absorbent and remove mechanically into containers. If necessary, dispose of adsorbed residues as required by regulations (see Section 13.)

**WATER SPILL:** Confine the spill immediately with booms. Notify relevant authorities. Remove from the surface by skimming or with suitable absorbents

**ENVIRONMENTAL PRECAUTIONS:** Prevent material from entering sewers, water sources or low lying areas; advise the relevant authorities if it has, or if it contaminates soil/vegetation.

Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

#### PERSONAL PROTECTIVE EQUIPMENT FOR SPILLS

**Eyes:** Use proper protection . safety glasses as a minimum

**Skin:** Washing at mealtime and end-of-shift is adequate

**Inhalation:** No respiratory protection should be needed for small spills. For large spills, use self-contained breathing apparatus or air-purifying respiratory protection according to established local/ site emergency response procedures.

Product Name: **Flash Point Reference Material  
– FPRM11**

Revision Date: *April 13, 2010*



Page 4 of 9

MSDS ref CII10-019

---

**Precautionary measures:** Avoid eye contact. Use reasonable care

<b>SECTION 7</b>	<b>HANDLING AND STORAGE</b>
------------------	-----------------------------

**HANDLING**

Keep container closed. Handle and open containers with care.

**ELECTROSTATIC ACCUMULATION HAZARD**

Yes, use proper bonding and/or grounding procedure. Additional information regarding safe handling of products with static accumulation potential can be ordered by contacting the American Petroleum Institute (API) for API Recommended Practice 2003, entitled "Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents" (American Petroleum Institute, 1220 L Street Northwest, Washington, DC 20005), or the National Fire Protection Association (NFPA) for NFPA 77 entitled "Static Electricity" (National Fire Protection Association, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101).

**STORAGE:**

Keep containers closed when not in use. Do not store in open or unlabelled containers. Store in a cool, well ventilated place, away from strong oxidizing agents and combustible materials. Do not store near heat, sparks, flame or strong oxidants.

**SPECIAL PRECAUTIONS**

Prevent small spills and leakages to optimize housekeeping, minimize fire risk and avoid slip hazards.

**EMPTY CONTAINER WARNING**

Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to refill or clean container since residue is difficult to remove. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

**STORAGE**

Use reasonable care and store away from oxidizing materials

<b>SECTION 8</b>	<b>EXPOSURE CONTROLS/PERSONAL PROTECTION</b>
------------------	--

**EXPOSURE LIMIT VALUES**

None established

**ENGINEERING CONTROLS**

The use of local exhaust ventilation is recommended to control process emissions near the source. Laboratory samples should be handled in a lab hood. Provide mechanical ventilation of confined spaces. See respiratory protection recommendations.

Product Name: **Flash Point Reference Material  
– FPRM11**

Revision Date: *April 13, 2010*



Page 5 of 9

MSDS ref CII10-019

## PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

### Respiratory Protection:

Where concentrations in air may exceed the limits given in this Section and engineering, work practice or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.

### Hand Protection:

Where contact may occur, wear long sleeves, and chemical resistant gloves, protective clothing and footwear

### Eye Protection:

Use proper protection . safety glasses as a minimum. For open systems where contact is likely, wear safety glasses with side shields. Where contact may occur, wear safety glasses with side shields.

### Specific Hygiene Measures:

Washing at mealtime and end-of-shift is usually adequate

<b>SECTION 9</b>	<b>PHYSICAL AND CHEMICAL PROPERTIES</b>
------------------	---

Typical physical and chemical properties are given below. Consult the Cannon Instrument Company as indicated in Section 1 for additional data.

## GENERAL INFORMATION

<b>Physical state:</b>	Liquid
<b>Form:</b>	Liquid
<b>Color:</b>	Clear colorless
<b>Odor:</b>	Characteristic petroleum odor
<b>Odor threshold:</b>	not available

## IMPORTANT HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

**Specific Gravity @ 60°F:** 0.74  
**Bulk density g/cc:** Not available  
**Density, kg/m<sup>3</sup> (lbs./gal.):** Not available  
**Flash point °C (°F) [method]:** 65°C (149°F) [ASTM D56]  
**Flammable limits (approx. Volume % in air) –** not available  
**Autoignition temperature °C (°F):** 205 °C (400 °F)  
**Ignition temperature (polymers) °C (°F):** not applicable  
**Boiling point/range °C (°F):** 196 °C (385 °F)  
**Vapor density (air =1):** 5.4  
**Vapor pressure @ 20°C, kPa (mm Hg):** 0.1 kPa  
**Evaporation rate (n-butyl acetate =1):** Not available

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. The information and recommendations contained herein is compiled from suppliers' MSDS and are accurate and reliable to the best of Cannon Instrument Company's knowledge and belief as of the indicated revision date. No representation, warranty or guarantee, however, is made with regards to accuracy, reliability or completeness. Conditions of use of the material are under the control of the user; therefore, it is the user's responsibility to determine the suitability and completeness of such information for any specific conditions/ use.

Product Name: **Flash Point Reference Material  
– FPRM11**

Revision Date: *April 13, 2010*



Page 6 of 9

MSDS ref CII10-019

**pH:** Not applicable  
**Log Pow (n-Octanol/water partition coefficient):** Not available  
**Solubility in water (20 °C):** negligible  
**Viscosity:** Not available

#### OTHER INFORMATION

**Freezing point °C (°F):** Not available  
**Melting Point °C (°F):** -10°C (14 °F)  
**Pour point °C (°F):** Not available  
**Molecular weight:** 156  
**Hygroscopic:** no  
**Coefficient of thermal expansion:** Not available

### SECTION 10 STABILITY AND REACTIVITY

**STABILITY:** Stable

**CONDITIONS TO AVOID:** Extreme heat and high energy sources of ignition.

**MATERIALS TO AVOID:** Halogens, molten sulfur, strong oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Product does not decompose at ambient temperatures.

**HAZARDOUS POLYMERIZATION:** Hazardous polymerization will not occur

### SECTION 11 TOXICOLOGICAL INFORMATION

Routes of Entry: Absorbed through skin. Eye contact. Inhalation.  
Toxicity to Animals: LD50: Not Available  
LC50: Not Available  
Chronic Effects on Humans **CARCINOGENIC EFFECTS:** Classified 4 ( No evidence.) by NTP, None by OSHA, None by NIOSH.  
Other Toxic Effects on Humans Hazardous in case of skin contact (irritant).  
Special Remarks on Toxicity to Animals Not available  
Special Remarks on Chronic Effects on Humans Not available  
Special Remarks on other Toxic Effects on Humans Not available

No specific toxicology data on this products have been provided by the supplier(s)

### SECTION 12 ECOLOGICAL INFORMATION

#### Environmental fate and distribution

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. The information and recommendations contained herein is compiled from suppliers' MSDS and are accurate and reliable to the best of Cannon Instrument Company's knowledge and belief as of the indicated revision date. No representation, warranty or guarantee, however, is made with regards to accuracy, reliability or completeness. Conditions of use of the material are under the control of the user; therefore, it is the user's responsibility to determine the suitability and completeness of such information for any specific conditions/ use.

Product Name: **Flash Point Reference Material  
– FPRM11**

Revision Date: *April 13, 2010*



Page 7 of 9

MSDS ref CII10-019

No specific ecological data are available for this product. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information

**Air:** No specific data are available

**Water:** No specific data are available

**Soil:** No specific data are available

**Degradation:** No specific data are available

#### **Environmental effects**

**Toxicity to water organisms:** No specific data are available

**Toxicity to soil organisms:** No specific data are available

**Bioaccumulation:** No specific data are available

#### **Fate and effects in water treatment plants**

No specific data are available

### **SECTION 13 DISPOSAL CONSIDERATIONS**

Please refer to Sections 5, 6 and 15 for disposal and regulatory information

**WASTE DISPOSAL :** Product is suitable for burning in an enclosed, controlled burner for fuel value. Such burning may be limited pursuant to the Resource Conservation and Recovery Act. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate government waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

### **SECTION 14 TRANSPORT INFORMATION**

**Note:** The information provided below may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations for additional requirements and mode-specific, material-specific, or quantity-specific shipping requirements.

#### **United States Department of Transportation (US DOT):**

UN/ID#	Proper Shipping Name	Class/Division	Hazard Label(s)	Packing Group
UN2330	Undecane	3	Flammable Liquid	III

#### **International Air Transport Association (IATA):**

Product Name: **Flash Point Reference Material  
- FPRM11**

Revision Date: *April 13, 2010*



Page 8 of 9

MSDS ref CII10-019

UN/ID#	Proper Shipping Name	Class/Division	Hazard Label(s)	Packing Group
UN2330	Undecane	3	Flammable Liquid	III

## SECTION 15 REGULATORY INFORMATION

**OSHA HAZARD COMMUNICATION STANDARD:** This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200. See section 2

### NATIONAL CHEMICAL INVENTORY LISTING:

This product, and/ or its constituents, is listed on the US EPA/ TSCA (Toxic Substances Control Act) Inventory

### COMMUNITY RTK:

Undecane (CAS# 1120-21-4) . 100%

### Clean Water Act/Oil Pollution Act:

No specific information provided by the supplier(s) of this product

### Section 304 CERCLA HAZARDOUS SUBSTANCES:

No specific information provided by the supplier(s) of this product

### SARA (311/312) REPORTABLE HAZARD CATEGORIES:

Under the provisions of Title III, Sections 311/312 of the Superfund Amendments and Reauthorization Act, this product is classified into the following hazard categories:  
Irritant, fire hazard (flammable)

### SARA (313) TOXIC RELEASE INVENTORY:

No specific information provided by the supplier(s) of this product

## International chemical inventories and hazard classifications

**This product and/ or its components are on the Canadian Domestic Substance List**

**WHMIS Classifications (Canada):**

B3 - Flammable and combustible material - Combustible liquid  
D2B - Poisonous and infectious material - Other Effects . Toxic



WHMIS Health Effects Criteria Met by this Chemical:

Product Name: **Flash Point Reference Material  
– FPRM11**

Revision Date: *April 13, 2010*



Page 9 of 9

MSDS ref CII10-019

D2B - Skin irritation - toxic - other  
WHMIS Ingredient Disclosure List:  
Not included. Meets criteria for disclosure at 1% or greater.

**This product and/ or its components are on EINECS (European Inventory of Existing Chemical Substances) and/ or ELINCS (European Library of Notified Chemical Substances)**

[EU Hazard Classification, risk and safety phrases \(Europe\):](#)



**X<sub>n</sub> Harmful**

R65: Harmful: may cause lung damage if swallowed  
R36/38: Irritating to eyes and skin  
S2: Keep out of reach of children  
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice  
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label  
S24/25: Avoid contact with skin and eyes  
S36/37: Wear suitable protective clothing and gloves

## SECTION 16

## OTHER INFORMATION

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

### Revision Summary:

- **October 15, 2005 -- This MSDS has been fully reviewed and reformatted to conform to changes in standard format**
- **January 8, 2007 – MSDS updated based on information from supplier**
- **February 15, 2007: Added Canadian and European classification and labeling information, based on current regulations and/or recommendations from suppliers (see Section 15)**
- **March 26, 2007: Updated and standardized format of Transport Information (see Section 14)**
- **April 13, 2010: Reviewed content. Updated OSHA Hazardous Substance(s) or Complex Substance(s) of Composition/Information on Ingredients (see Section 2).**

### NOTES: