

Product Name: **Flash Point Reference Material
– FPRM16**

Revision Date: *May 5, 2010*



Page 1 of 9

MSDS ref CII10-021

MATERIAL SAFETY DATA SHEET

SECTION 1

PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product name: **Flash Point Reference Material – FPRM16**

Alternate description/ brand: FPRM16

Product description: Hexadecane; hydrocarbon liquid

Product code: 9727-A25

Intended use: Flash Point Reference standard

COMPANY IDENTIFICATION

Supplier: Cannon Instrument Company

2139 High Tech Road

State College, Pennsylvania 16803

Product Technical Information: (814) 353-8000

Product MSDS Information: (814) 353-8000

EMERGENCY TELEPHONE NUMBER:

24-Hour Transportation Emergency: (800) 255-3924 Domestic CHEM-TEL Inc.

24-Hour Health Emergency: +1 (813) 248-0585 Overseas CHEM-TEL Inc. (please call collect)

SECTION 2

COMPOSITION/INFORMATION ON INGREDIENTS

OSHA Hazardous Substance(s) or Complex Substance(s)

This product is hazardous as defined in 29 CFR1910.1200, based on the following:

OSHA HAZARD

COMPONENT

Combustible

Hexadecane

Irritant

Hexadecane

SECTION 3

HAZARD IDENTIFICATION

EFFECTS OF OVEREXPOSURE:

Acute effects

Eye: Irritant

Skin: Irritant; can be absorbed through the skin

Inhalation: High vapor/aerosol concentrations (attainable at elevated temperatures) are irritating to the eyes and the respiratory tract, and may cause headaches, dizziness, anaesthesia, drowsiness, unconsciousness, and other central nervous system effects. This substance is unlikely to present a significant inhalation hazard if used for the recommended purpose.

Product Name: **Flash Point Reference Material
– FPRM16**

Revision Date: *May 5, 2010*



Page 2 of 9

MSDS ref CII10-021

Oral: Low toxicity. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause severe pulmonary injury, possibly progressing to death.

Prolonged/ repeated exposure effects

Chronic effects

None identified

Signs and symptoms of overexposure:

Irritation and/ or redness of eyes and skin

Medical conditions aggravated by exposure

None identified

NFPA HAZARD ID: Health: 2 Flammability: 1 Reactivity: 0
(National Fire Protection Association)

NOTE: This material should not be used for any other purpose than the intended use in Section 1

SECTION 4 FIRST AID MEASURES

INHALATION Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

SKIN CONTACT Flush with large amounts of water; use soap if available. Remove grossly contaminated clothing, including shoes, and launder before reuse.

EYE CONTACT Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

INGESTION If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

NOTE TO PHYSICIAN: Ingested material, if aspirated into the lungs, may cause chemical pneumonitis.

SECTION 5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Appropriate extinguishing media: Carbon dioxide, foam, dry chemical and water fog. Water can be used to cool fire exposed containers

FIRE FIGHTING

Fire fighting instructions: Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boilover. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance

Product Name: **Flash Point Reference Material
– FPRM16**

Revision Date: *May 5, 2010*



Page 3 of 9

MSDS ref CII10-021

along the ground or surface to ignition sources where they may ignite or explode.

Unusual fire hazards: None identified

Hazardous combustion products: Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products

GENERAL HAZARD

Combustible Liquid can form combustible mixtures at temperatures at or above the flashpoint. Static Discharge: Material can accumulate static charges which can cause an incendiary electrical discharge. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

FLAMMABILITY PROPERTIES

Flash point °C (°F) [method]: 112°C (234°F)

Flammable limits (approx. Volume % in air) – not available

Autoignition temperature °C (°F): 202 °C (396 °F)

SECTION 6 ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES : Report spills/releases to appropriate authorities as required.

CONTAINMENT/ CLEANUP

PROCEDURES IF MATERIAL IS RELEASED OR SPILLED:

LAND SPILL: Shut off source taking normal safety precautions. Take measures to minimize the effects on ground water. Recover by pumping (use an explosion proof or hand pump) or contain spilled material with sand or other suitable absorbent and remove mechanically into containers. If necessary, dispose of adsorbed residues as required by regulations (see Section 13.)

WATER SPILL: Confine the spill immediately with booms. Notify relevant authorities. Remove from the surface by skimming or with suitable absorbents

ENVIRONMENTAL PRECAUTIONS: Prevent material from entering sewers, water sources or low lying areas; advise the relevant authorities if it has, or if it contaminates soil/vegetation.

Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

PERSONAL PROTECTIVE EQUIPMENT FOR SPILLS

Eyes: Use proper protection . safety glasses as a minimum

Skin: Washing at mealtime and end-of-shift is adequate

Inhalation: No respiratory protection should be needed for small spills. For large spills, use self-contained breathing apparatus or air-purifying respiratory protection according to established local/ site emergency response procedures.

Product Name: **Flash Point Reference Material
– FPRM16**

Revision Date: *May 5, 2010*



Page 4 of 9

MSDS ref CII10-021

Precautionary measures: Avoid eye contact. Use reasonable care

SECTION 7	HANDLING AND STORAGE
------------------	-----------------------------

HANDLING

Keep container closed. Handle and open containers with care.

ELECTROSTATIC ACCUMULATION HAZARD

Yes, use proper bonding and/or grounding procedure. Additional information regarding safe handling of products with static accumulation potential can be ordered by contacting the American Petroleum Institute (API) for API Recommended Practice 2003, entitled "Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents" (American Petroleum Institute, 1220 L Street Northwest, Washington, DC 20005), or the National Fire Protection Association (NFPA) for NFPA 77 entitled "Static Electricity" (National Fire Protection Association, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101).

STORAGE:

Keep containers closed when not in use. Do not store in open or unlabelled containers. Store in a cool, well ventilated place, away from strong oxidizing agents and combustible materials. Do not store near heat, sparks, flame or strong oxidants.

SPECIAL PRECAUTIONS

Prevent small spills and leakages to optimize housekeeping, minimize fire risk and avoid slip hazards.

EMPTY CONTAINER WARNING

Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to refill or clean container since residue is difficult to remove. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

STORAGE

Use reasonable care and store away from oxidizing materials

SECTION 8	EXPOSURE CONTROLS/PERSONAL PROTECTION
------------------	--

EXPOSURE LIMIT VALUES

None established

ENGINEERING CONTROLS

The use of local exhaust ventilation is recommended to control process emissions near the source. Laboratory samples should be handled in a lab hood. Provide mechanical ventilation of confined spaces. See respiratory protection recommendations.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection:

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. The information and recommendations contained herein is compiled from suppliers' MSDS and are accurate and reliable to the best of Cannon Instrument Company's knowledge and belief as of the indicated revision date. No representation, warranty or guarantee, however, is made with regards to accuracy, reliability or completeness. Conditions of use of the material are under the control of the user; therefore, it is the user's responsibility to determine the suitability and completeness of such information for any specific conditions/ use.

Product Name: **Flash Point Reference Material
– FPRM16**

Revision Date: *May 5, 2010*



Page 5 of 9

MSDS ref CII10-021

Where concentrations in air may exceed the limits given in this Section and engineering, work practice or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.

Hand Protection:

Where contact may occur, wear long sleeves, and chemical resistant gloves, protective clothing and footwear

Eye Protection:

Use proper protection . safety glasses as a minimum. For open systems where contact is likely, wear safety glasses with side shields. Where contact may occur, wear safety glasses with side shields.

Specific Hygiene Measures:

Washing at mealtime and end-of-shift is usually adequate

SECTION 9	PHYSICAL AND CHEMICAL PROPERTIES
------------------	---

Typical physical and chemical properties are given below. Consult the Cannon Instrument Company as indicated in Section 1 for additional data.

GENERAL INFORMATION

Physical state:	Liquid
Form:	Liquid
Color:	Clear colorless
Odor:	Characteristic petroleum odor
Odor threshold:	not available

IMPORTANT HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Specific Gravity @ 60°F: 0.8
Bulk density g/cc: Not available
Density, kg/m³ (lbs./gal.): Not available
Flash point °C (°F) [method]: 112 °C (224 °F)
Flammable limits (approx. Volume % in air) – not available
Ignition temperature (polymers) °C (°F): not applicable
Autoignition temperature °C (°F): 202 °C (396 °F)
Boiling point/range °C (°F): 285 °C (545 °F)
Vapor density @ 101 kPa (air =1): Greater than air
Vapor pressure @ 20°C, kPa (mm Hg): 0.003 mm Hg @ 25 °C
Evaporation rate (n-butyl acetate =1): Not available
pH: not applicable
Log Pow (n-Octanol/water partition coefficient): Not available
Solubility in water (20 °C): negligible
Viscosity: 3 cSt @ 37.78 °C / 3 mm²/s

OTHER INFORMATION

Freezing point °C (°F): Not available
Melting Point °C (°F): 23°C (73 °F)

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. The information and recommendations contained herein is compiled from suppliers' MSDS and are accurate and reliable to the best of Cannon Instrument Company's knowledge and belief as of the indicated revision date. No representation, warranty or guarantee, however, is made with regards to accuracy, reliability or completeness. Conditions of use of the material are under the control of the user; therefore, it is the user's responsibility to determine the suitability and completeness of such information for any specific conditions/ use.

Product Name: **Flash Point Reference Material
– FPRM16**

Revision Date: *May 5, 2010*



Page 6 of 9

MSDS ref CII10-021

Pour point °C (°F):	Not available
Molecular weight:	227
Hygroscopic:	No
Coefficient of thermal expansion:	Not available

SECTION 10	STABILITY AND REACTIVITY
-------------------	---------------------------------

STABILITY: Stable

CONDITIONS TO AVOID: Extreme heat and high energy sources of ignition.

MATERIALS TO AVOID: Halogens, molten sulfur, strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Product does not decompose at ambient temperatures.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur

SECTION 11	TOXICOLOGICAL INFORMATION
-------------------	----------------------------------

No specific toxicology data on this products have been provided by the supplier(s)

SECTION 12	ECOLOGICAL INFORMATION
-------------------	-------------------------------

Environmental fate and distribution

No specific ecological data are available for this product. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information

Air: No specific data are available

Water: No specific data are available

Soil: No specific data are available

Degradation: No specific data are available

Environmental effects

Toxicity to water organisms: No specific data are available

Toxicity to soil organisms: No specific data are available

Bioaccumulation: No specific data are available

Fate and effects in water treatment plants

No specific data are available

Product Name: **Flash Point Reference Material
– FPRM16**

Revision Date: *May 5, 2010*



SECTION 13 DISPOSAL CONSIDERATIONS

Please refer to Sections 5, 6 and 15 for disposal and regulatory information

WASTE DISPOSAL : Product is suitable for burning in an enclosed, controlled burner for fuel value. Such burning may be limited pursuant to the Resource Conservation and Recovery Act. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate government waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

SECTION 14 TRANSPORT INFORMATION

Note: The information provided below may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations for additional requirements and mode-specific, material-specific, or quantity-specific shipping requirements.

United States Department of Transportation (US DOT):

UN/ID#	Proper Shipping Name	Class/Division	Hazard Label(s)	Packing Group
Not Regulated As A Hazardous Material Or Dangerous Good For This Mode of Transportation.				

International Air Transport Association (IATA):

UN/ID#	Proper Shipping Name	Class/Division	Hazard Label(s)	Packing Group
Not Regulated As A Hazardous Material Or Dangerous Good For This Mode of Transportation.				

SECTION 15 REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD: This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200. See section 2

NATIONAL CHEMICAL INVENTORY LISTING:

This product, and/ or its constituents, is listed on the US EPA/ TSCA (Toxic Substances Control Act) Inventory

COMMUNITY RTK:

Hexadecane (CAS# 544-76-3) . 100%

Clean Water Act/Oil Pollution Act:

No specific information provided by the supplier(s) of this product

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. The information and recommendations contained herein is compiled from suppliers' MSDS and are accurate and reliable to the best of Cannon Instrument Company's knowledge and belief as of the indicated revision date. No representation, warranty or guarantee, however, is made with regards to accuracy, reliability or completeness. Conditions of use of the material are under the control of the user; therefore, it is the user's responsibility to determine the suitability and completeness of such information for any specific conditions/ use.

Product Name: **Flash Point Reference Material
– FPRM16**

Revision Date: *May 5, 2010*



Page 8 of 9

MSDS ref CII10-021

Section 304 CERCLA HAZARDOUS SUBSTANCES:

No specific information provided by the supplier(s) of this product

SARA (311/312) REPORTABLE HAZARD CATEGORIES:

Under the provisions of Title III, Sections 311/312 of the Superfund Amendments and Reauthorization Act, this product is classified into the following hazard categories:
Irritant, fire hazard.

SARA (313) TOXIC RELEASE INVENTORY:

No specific information provided by the supplier(s) of this product

International chemical inventories and hazard classifications

This product and/ or its components are on the Canadian Domestic Substance List/ Non-Domestic Substances List (DSL/ NDSL)

[WHMIS Classifications \(Canada\):](#)

D2B - Poisonous and infectious material - Other Effects . Toxic



Skin or eye irritation

This product and/ or its components are on EINECS (European Inventory of Existing Chemical Substances) and/ or ELINCS (European Library of Notified Chemical Substances)

[EU Hazard Classification, risk and safety phrases \(Europe\):](#)



Xn

R38: Irritating to skin

R65: Harmful: may cause lung damage if swallowed

R67: Vapors may cause drowsiness or dizziness

S2: Keep out of reach of children

S24: Avoid contact with the skin

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label

S36/37: Wear suitable protective clothing and gloves

SECTION 16

OTHER INFORMATION

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Revision Summary:

- **October 15, 2005 -- This MSDS has been fully reviewed and reformatted to conform to changes in standard format**

Product Name: **Flash Point Reference Material**
– FPRM16

Revision Date: *May 5, 2010*



Page 9 of 9

MSDS ref CII10-021

-
- **February 27, 2007: Added Canadian and European classification and labeling information, based on current regulations and/or recommendations from suppliers (see Section 15)**
 - **April 25, 2007: Updated and standardized format of Transport Information (see Section 14)**
 - **May 5, 2010: Reviewed content. Updated NFPA Hazard ID of Hazard Identification (see Section 3). Updated Flammability Properties of Fire-Fighting Measures (see Section 5). Updated Important Health, Safety, and Environmental Information and Other Information of Physical and Chemical Properties (see Section 9). Updated International Chemical Inventories and Hazard Classifications of Regulatory Information (see Section 15).**

NOTES: