

Product Name: **Bath Oil – Petroleum White Oil**



Revision Date: *March 3, 2011*

Page 1 of 8

MSDS ref CII11-025

MATERIAL SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product name: Bath Oil – Petroleum White Oil

Alternate description/ brand: Not applicable

Product description: Highly refined mineral white oil

Product code: 9726-L20

Intended use: Constant temperature bath oil

COMPANY IDENTIFICATION

Supplier: Cannon Instrument Company

2139 High Tech Road

State College, Pennsylvania 16803

Product Technical Information: (814) 353-8000

Product MSDS Information: (814) 353-8000

EMERGENCY TELEPHONE NUMBER:

24-Hour Transportation Emergency: (800) 255-3924 Domestic CHEM-TEL Inc.

24-Hour Health Emergency: +1 (813) 248-0585 Overseas CHEM-TEL Inc. (please call collect)

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

- OSHA Hazardous Substance(s) or Complex Substance(s)

Eye irritant, skin irritant

Chemical Name	Wt. %	CAS
BHT (Butylated Hydroxytoluene)	< 1	128-37-0

SECTION 3 HAZARD IDENTIFICATION

This product is a mixture that has not been tested in laboratory animals. The following is based on characterizations of components as provided by suppliers

EFFECTS OF OVEREXPOSURE:

Acute effects

Eye: Eye irritant

Skin: Skin irritant

Inhalation: No significant effects expected from a single short-term exposure. Inhalation exposures are not expected under recommended uses/ conditions

Product Name: **Bath Oil – Petroleum White Oil**



Revision Date: *March 3, 2011*

Page 2 of 8
MSDS ref CII11-025

Oral: Low ingestion hazard in normal use. If ingested, do not induce vomiting.

Prolonged/ repeated exposure effects

Skin: Irritating to the skin

Inhalation: Not classified as hazardous

Oral: Not classified as hazardous

Repeated and/or prolonged exposure may cause irritation to the skin, eyes or respiratory tract. The base oils in this product are severely solvent refined and/or severely hydrotreated. Chronic mouse skin painting studies of severely treated oils show no evidence of carcinogenic effects.

Signs and symptoms of overexposure:

Irritation and/ or redness of eyes and skin

Medical conditions aggravated by exposure

None identified

NFPA HAZARD ID: Health: 1 Flammability: 1 Reactivity: 0
(National Fire Protection Association)

NOTE: This material should not be used for any other purpose than the intended use in Section 1

SECTION 4	FIRST AID MEASURES
------------------	---------------------------

INHALATION	Not expected to be a problem since high temperature or high mechanical shear are required to generate airborne exposure. However, if respiratory irritation, dizziness, nausea, or unconsciousness occurs due to excessive vapor or mist exposure, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or mouth-to-mouth resuscitation.
SKIN CONTACT	Wash contact areas with soap and water. Remove and clean oil soaked clothing daily and wash affected area.
EYE CONTACT	Flush thoroughly with water. If irritation occurs, call a physician.
INGESTION	Seek medical attention. Do not induce vomiting.

NOTE TO PHYSICIAN: Ingested material, if aspirated into the lungs, can cause chemical pneumonitis.

SECTION 5	FIRE-FIGHTING MEASURES
------------------	-------------------------------

EXTINGUISHING MEDIA

Appropriate extinguishing media: Carbon dioxide, foam, dry chemical and water fog. Water can be

Product Name: **Bath Oil – Petroleum White Oil**



Revision Date: *March 3, 2011*

Page 3 of 8

MSDS ref CII11-025

used to cool fire exposed containers

FIRE FIGHTING

Fire fighting instructions: Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep the exposed containers cool. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

Unusual fire hazards: None identified

Hazardous combustion products: Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products

FLAMMABILITY PROPERTIES

Flash point °C (°F) [method]: ~ 230°C (~445 °F) [Closed Cup]

Flammable limits (approx. Volume % in air): not determined

Autoignition temperature °C (°F): not determined

SECTION 6 ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES : Report spills/releases to appropriate authorities as required.

CONTAINMENT/ CLEANUP

PROCEDURES IF MATERIAL IS RELEASED OR SPILLED:

LAND SPILL: Shut off source taking normal safety precautions. Take measures to minimize the effects on ground water. Recover by pumping or contain spilled material with sand or other suitable absorbent and remove mechanically into containers. If necessary, dispose of adsorbed residues as required by regulations (see Section 13.)

WATER SPILL: Confine the spill immediately with booms. Notify relevant authorities. Remove from the surface by skimming or with suitable absorbents

ENVIRONMENTAL PRECAUTIONS: Prevent material from entering sewers, water sources or low lying areas; advise the relevant authorities if it has, or if it contaminates soil/vegetation.

PERSONAL PROTECTIVE EQUIPMENT FOR SPILLS

Eyes: Use proper protection . safety glasses as a minimum

Skin: Washing at mealtime and end-of-shift is adequate

Inhalation: No respiratory protection should be needed

Precautionary measures: Avoid eye contact. Use reasonable care

SECTION 7 HANDLING AND STORAGE

HANDLING

Avoid prolonged/ repeated skin contact. Use with adequate ventilation

STORAGE:

Keep containers closed when not in use. Do not store in open or unlabelled containers. Store

away from strong oxidizing agents and combustible materials. Do not store near heat, sparks, flame or strong oxidants.

SPECIAL PRECAUTIONS

Prevent small spills and leakages to optimize housekeeping and avoid slip hazard.

EMPTY CONTAINER WARNING

Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to refill or clean container since residue is difficult to remove. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

STORAGE

Use reasonable care and store away from oxidizing materials

SECTION 8	EXPOSURE CONTROLS/PERSONAL PROTECTION
------------------	--

EXPOSURE LIMIT VALUES

When mists/aerosols can occur, the following are recommended:

- 5 mg/m³ (as oil mist) - ACGIH Threshold Limit Value (TLV)
- 10 mg/m³ (as oil mist) - ACGIH Short Term Exposure Limit (STEL)
- 5 mg/m³ (as oil mist) . OSHA Permissible Exposure Limit (PEL)

ENGINEERING CONTROLS

General ventilation is recommended. No local exhaust ventilation should be needed

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection:

No respiratory protection should be needed

Hand Protection:

Impervious gloves

Eye Protection:

Use proper protection . safety glasses as a minimum

Specific Hygiene Measures:

Washing at mealtime and end-of-shift is adequate

SECTION 9	PHYSICAL AND CHEMICAL PROPERTIES
------------------	---

Typical physical and chemical properties are given below. Consult the Cannon Instrument Company as indicated

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. The information and recommendations contained herein is compiled from suppliers' MSDS and are accurate and reliable to the best of Cannon Instrument Company's knowledge and belief as of the indicated revision date. No representation, warranty or guarantee, however, is made with regards to accuracy, reliability or completeness. Conditions of use of the material are under the control of the user; therefore, it is the user's responsibility to determine the suitability and completeness of such information for any specific conditions/ use.

Product Name: **Bath Oil – Petroleum White Oil**



Revision Date: *March 3, 2011*

Page 5 of 8
MSDS ref CII11-025

in Section 1 for additional data.

GENERAL INFORMATION

Physical state: Liquid
Form: Liquid
Color: clear colorless
Odor: Odorless or very slight characteristic petroleum odor
Odor threshold: not available

IMPORTANT HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Specific Gravity @ 25°C: Lighter than water
Bulk density g/cc: not determined
Density, kg/m³ (lbs./gal.): not determined
Flash point °C (°F) [method]: ~ 230 °C (~445 °F) [Closed Cup]
Flammable limits (approx. Volume % in air) - not determined
Ignition temperature (polymers) °C (°F): not applicable
Autoignition temperature °C (°F): not determined
Boiling point/range °C (°F): not determined
Vapor density @ 101 kPa (air =1): not determined
Vapor pressure @ 20°C, kPa (mm Hg): not determined
Evaporation rate (n-butyl acetate =1): not determined
pH: not applicable
Log Pow (n-Octanol/water partition coefficient): not determined
Solubility in water (20 °C): negligible
Viscosity: not determined

OTHER INFORMATION

Freezing point °C (°F): not determined
Melting Point °C (°F): not determined
Pour point °C (°F): not determined
Molecular weight: not available
Hygroscopic: no
Coefficient of thermal expansion: not determined

SECTION 10 STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: Extreme heat and high energy sources of ignition.

MATERIALS TO AVOID: Strong oxidizing agents/ materials can cause a reaction

HAZARDOUS DECOMPOSITION PRODUCTS: Product does not decompose at ambient temperatures.

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur

SECTION 11 TOXICOLOGICAL INFORMATION

Product Name: **Bath Oil – Petroleum White Oil**



Revision Date: *March 3, 2011*

Page 6 of 8

MSDS ref CII11-025

This product is a mixture of components, and it has not been tested. Information from suppliers indicates that the product is classified as a skin and eye irritant, based on the BHT additive which is present at <1%. Canadian WHMIS and the European Union classification and labeling criteria do not require that this preparation be classified as hazardous/ dangerous

SECTION 12	ECOLOGICAL INFORMATION
-------------------	-------------------------------

Environmental fate and distribution

No specific environmental data are available for this product; this assessment is based on information for similar components/ products.

Air: This product has a low vapor pressure. As a result, it is unlikely to become an atmospheric contaminant under recommended conditions of use

Water: This product has low water solubility. Since it has a specific gravity of <1, if discharged to water, it will form a surface film. As the product is non-volatile and has a high binding affinity for particulate matter, it will absorb to particulates and form sediment.

Soil: This product is expected to have a high binding affinity for particulate matter in soil

Degradation: This product is expected to be inherently biodegradable.

Environmental effects

Toxicity to water organisms: Based on analogy to similar materials, this product is expected to exhibit low toxicity to aquatic organisms

Toxicity to soil organisms: No available information

Bioaccumulation: Bioaccumulation is unlikely due to the very low water solubility of this product; therefore bioavailability to aquatic organisms is minimal

Fate and effects in water treatment plants

This product or similar products have been shown to be non-toxic to sewage sludge bacteria

SECTION 13	DISPOSAL CONSIDERATIONS
-------------------	--------------------------------

When a decision is made to discard this material, it is not considered a hazardous waste under Resource Conservation and Recovery Act (RCRA).

State or local laws may impose additional regulatory requirements regarding disposal

WASTE DISPOSAL : Product is suitable for burning in an enclosed, controlled burner for fuel value. Such burning may be limited pursuant to the Resource Conservation and Recovery Act. In addition, the product is suitable for processing by an approved recycling facility or can be

Product Name: **Bath Oil – Petroleum White Oil**



Revision Date: *March 3, 2011*

Page 7 of 8

MSDS ref CII11-025

disposed of at an appropriate government waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

SECTION 14 TRANSPORT INFORMATION

Note: The information provided below may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations for additional requirements and mode-specific, material-specific, or quantity-specific shipping requirements.

United States Department of Transportation (US DOT):

UN/ID#	Proper Shipping Name	Class/Division	Hazard Label(s)	Packing Group
Not Regulated As A Hazardous Material Or Dangerous Good For This Mode of Transportation.				

International Air Transport Association (IATA):

UN/ID#	Proper Shipping Name	Class/Division	Hazard Label(s)	Packing Group
Not Regulated As A Hazardous Material Or Dangerous Good For This Mode of Transportation.				

SECTION 15 REGULATORY INFORMATION

OSHA HAZARD COMMUNICATION STANDARD: When used for its intended purposes, this material is classified as a skin and eye irritant, in accordance with OSHA 29 CFR 1910.1200.

NATIONAL CHEMICAL INVENTORY LISTING: This product, and/ or its constituents, is listed on the US EPA/ TSCA (Toxic Substances Control Act) Inventory

COMMUNITY RTK:

Chemical Name	CAS Number	Typical Value	Component TPQ	Product TPQ
Highly refined mineral white oil	8042-47-5	> 99%	Not applicable	Not applicable
BHT (Butylated Hydroxytoluene)	128-37-0	< 1%	Not applicable	Not applicable

Section 304 CERCLA HAZARDOUS SUBSTANCES:

This product contains no chemicals that are classified as hazardous under CERCLA

SARA (311/312) REPORTABLE HAZARD CATEGORIES:

This product contains no chemicals that are classified as hazardous under SARA 312

SARA (313) TOXIC RELEASE INVENTORY:

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. The information and recommendations contained herein is compiled from suppliers' MSDS and are accurate and reliable to the best of Cannon Instrument Company's knowledge and belief as of the indicated revision date. No representation, warranty or guarantee, however, is made with regards to accuracy, reliability or completeness. Conditions of use of the material are under the control of the user; therefore, it is the user's responsibility to determine the suitability and completeness of such information for any specific conditions/ use.

Product Name: **Bath Oil – Petroleum White Oil**



Revision Date: *March 3, 2011*

Page 8 of 8

MSDS ref CII11-025

This product contains no chemicals that are regulated under SARA 313

International chemical inventories and hazard classifications

This product and/ or its components are on the Canadian Domestic Substance List/ NDSL, or are otherwise in compliance with related regulations.

[WHMIS Classifications \(Canada\):](#)

This series of fluids is not controlled under provisions of WHMIS

This product and/ or its components are on EINECS (European Inventory of Existing Chemical Substances) and/ or ELINCS (European Library of Notified Chemical Substances), or is otherwise in conformance with related EU directives/ regulations.

[EU Hazard Classification, risk and safety phrases \(Europe\):](#)

This series of fluids is not classified as dangerous according to EU directives and regulations.

SECTION 16	OTHER INFORMATION
-------------------	--------------------------

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Revision Summary:

- **October 15, 2005 -- This MSDS has been fully reviewed and reformatted to conform to changes in standard format**
- **March 7, 2007: Added Canadian and European classification and labeling information, based on current regulations and/or recommendations from suppliers (see Section 15)**
- **February 4, 2008: Added OSHA classification as a skin and eye irritant, based on information provided in the suppliers 2007 updated MSDS**
- **February 5, 2008: Added BHT and CAS# for refined mineral white oil to Community RTK (see Section 15). Updated and standardized format of Transport Information (see Section 14).**
- **March 6, 2008: Clarified wording of Section 304/CERCLA chemical classification in Regulatory Information (see Section 15)**
- **March 3, 2011: Reviewed content. Updated Flammability Properties of Fire-Fighting Measures (see Section 5). Updated Important Health, Safety, and Environmental Information of Physical and Chemical Properties (see Section 9).**

NOTES: